



TABLE OF CONTENTS

183 WINBAG®

184 WINBAG® CONNECT

185 WINBAG® MINI

186 WINBAG® MAX



ASTON

ASTON

ASTON

WINBAG FOR WINDOW FITTING

FOR PROFESSIONAL FITTING OF WINDOWS AND DOORS

General information about WINBAG


WINBAG is a fully tested quality product made from durable materials. However the WINBAG may be punctured by sharp objects such as screws and drills. Therefore should windows be secured at all times during fastening. It is important to keep in mind that the tool should only be considered an auxiliary tool during the fastening. The WINBAG is common used for numerous installation, adjustment and lifting tasks are produced in Denmark and patented in many countries worldwide.

For more information: www.winbag.dk



INSTALLATION

Installation instructions for window fitting




1 FIXATION

The window is fixated with one WINBAG at the top resting on two blocks in the bottom. The window should now be just as tight as it can still be adjusted.



2 ADJUSTMENT – in/ out

Now the window is adjusted in and out first in the bottom and thereafter in the top in proportion to the facade. This is done by pulling or pushing the window simultaneously with letting a bit of air out of the WINBAG at the top.



3 ADJUSTMENT side-ways

The WINBAGs are placed by the sides of the window near the top and bottom. With a leveler the adjustment takes place side-ways by adjusting the amount of air in the WINBAGs.



4 FASTENING

The window can now be fixed in the normal manner while the air filled WINBAGs keeps the window in position. At last the WINBAGs can be removed by letting out the air.

WINBAG®

FOR INSTALLATION OF WINDOWS AND DOORS

- Window fitting is done quick, effective and millimeter precise - one man can easily do the job alone – also large window sections
- The WINBAG can be used multiple times
- The WINBAG is a soft air cushion which does not leave marks and protects the frame
- Strong and well tested product with carrying capacity up to 135 kg.
- Made of fiber reinforced material for excellent durability
- Also available in sets of four Winbags incl. belt hook and manual

PRODUCT RANGE

MG:12 PG:2500 WINBAG®



Art.no.	Item name	Sealing width [mm]	Pcs/box
16782	WINBAG	2 - 50	1
12305	WINBAG-SET		4

WINBAG® CONNECT

FOR INSTALLATION OF WINDOWS AND DOORS

- WINBAG® CONNECT has an attached connector allowing for more WINBAGs to be connected together for more lifting power
- WINBAGs can be locked together in endless combinations
- One WINBAG® CONNECT can lift up to 135 kg
- Recommended maximum load capacity is 450 kg, which is 5 WINBAGs.
- Connectors can be bought separately
- Made of fiber reinforced material for excellent durability



PRODUCT RANGE

MG:12 PG:2500 WINBAG® CONNECT



Art.no.	Item name	Sealing width [mm]	Pcs/box
17636	WINBAG CONNECT	2 - 50	1
17687	WINBAG CONNECTOR	-	5

WINBAG® MINI

FOR INSTALLATION OF WINDOWS AND DOORS

- Small and versatile WINBAG® for fitting very tight spaces
- Allows very precise adjustability
- Soft cushion which does not leave any marks and protects the project
- WINBAG® MINI can lift up to 70 kg
- Made of fiber reinforced material for excellent durability

PRODUCT RANGE

MG:12 PG:2500 WINBAG® MINI



Art.no.	Item name	Sealing width [mm]	Pcs/box
17599	WINBAG MINI	2 - 40	1

WINBAG® MAX

FOR INSTALLATION OF WINDOWS AND DOORS

- The biggest and strongest of all WINBAGs
- Can lift up to 250 kg
- Long hose with suction cup for easy installation
- Made of fiber reinforced material for excellent durability

PRODUCT RANGE

MG:12 PG:2500 WINBAG® MAX



Art.no.	Item name	Sealing width [mm]	Pcs/box
18086	WINBAG MAX	2 - 70	1

ASTON
SWEDEN

ASTON SWEDEN AB
Hangarvägen 23
691 35 Karlskoga
Sweden

Tel +46 586 21 66 00

info@astonsweden.com
www.astonsweden.com